

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 July 2004 (29.07.2004)


PCT

(10) International Publication Number
WO 2004/064108 A2

- (51) International Patent Classification⁷: **H01L** **LEHTIMAKI, Kirsti, Elina** [FI/GB]; 3A Probert Road, London SW2 1BN (GB).
- (21) International Application Number: **PCT/GB2004/000060** (74) Agents: **ATKINSON, Ralph et al.**; Atkinson Burrington, 28 President Buildings, President Way, Sheffield S4 7UR (GB).
- (22) International Filing Date: 9 January 2004 (09.01.2004)
- (25) Filing Language: English (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (26) Publication Language: English
- (30) Priority Data: 0300683.0 11 January 2003 (11.01.2003) GB (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, CZ, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW).
- (71) Applicant (for all designated States except US): **ELEKSEN LIMITED** [GB/GB]; Charter Court, Midland Road, Hemel Hempstead, Hertfordshire HP2 5GE (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **SANDBACH, David, Lee** [GB/GB]; Flat C, 9 Westbourne Road, London N7 8AR (GB). **WALKINGTON, Stuart, Mark** [GB/GB]; 72A Westfields, St Albans, Hertfordshire AL3 4LZ (GB).

[Continued on next page]

(54) Title: MANUALLY DEFORMABLE INPUT DEVICE



(57) Abstract: A manually deformable input device responsive to manually applied pressure. The input device comprises a deformable electroconductive material (602) configured to exhibit changes in conductance (resistance) in response to being stretched or compressed, from which an extent of manually applied pressure can be determined. An electrical interface device (604) is configured to supply electrical current through the electroconductive material (602) via a first terminal (605) and a second terminal (606), and the input device further comprises a third terminal (607) connected at a position intermediate the first and second terminals. The electrical interface device (604) is configured to receive a voltage from the third terminal (607), which is representative of a proportion of voltage drop across the electroconductive material (602). The input device operates as a potential divider sensitive to manual operation irrespective of the absolute conductance (resistance) of the electroconductive material (602).

WO 2004/064108 A2



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- without international search report and to be republished upon receipt of that report